

Photographic LENSES SHUTTERS

Catalog No. 33



For Better Photographs

WITH consistent earnestness and ambition to meet the new day demands in photography, we have developed a line of photographic lenses that is complete for every need. The skillful precision and care that enter into the manufacturing of each lens permits us to offer superior quality. Only high grade artisans, best materials and the finest optical glass procurable enter into the making of Wollensak lenses. For more than thirty years Wollensak lenses

have occupied an enviable position in the field and are in constant use by the better photographers throughout the world who manifest keen delight and complete satisfaction. As the quality in a lens contributes greatly

to the distinctiveness of the finished photograph, intelligent care should be used in selecting a lens that is best suited for the purpose. As specialists in photographic lenses and shutters, we solicit the opportunity of making recommendations and serving your requirements.



Series Ia 16.3-17.7

THREE fine anastigmats in one. Both the long-focus single elements may be used alone, and they, like the doublet, are fully corrected anastigmats. The triple-convertible feature is of infinite value in obtaining telephoto effects, better perspective, or a larger image from a given point of view.

The commercial photographer or advanced amateur who wants the maximum of convenience and versatility, will find the Series Ia a mighty fine investment, for in buying it he obtains three perfect anastigmats for little more than the price of one.

| No. | Size | Equiv. Focus Inch | Front Focus Inch | Rear Focus Inch | Speed f. | In Barrel | In Betax |
|-------------------------|----------------------------------|---------------------------------|------------------------|-----------------------|----------|------------------|------------------|
| 1 1a | 314x 414 314x 414 | 434 518 534 534 619 | 814 | 814 814 | 6.3 | \$43.50 | \$45.50 |
| 2 | 4 x 5 | 535 | 10 | 10 | 6.8 | 47.50 50.00 | 49.50 54.00 |
| 2 2a | 4 x 5 | 534 | 1234 | 834 | 7.7 | 52,50 | 56,50 |
| 2b | 4 x 5 | 63/2 | 1234 | 10 | 6.8 | 55.00 | 59.00 |
| 3a | 4 x 5 5 x 7 5 x 7 5 x 8 | 714 | 1234 | 1234 | 6.3 | 61.50 | -70.50 68.50 |
| -3b | 5 x 8 | 714 814 834 9 | 1516 | 1232 | 6.8 | 72.00 | 78.00 |
| 3e | 5 x 8 | 834 | 20 | 1234 | 7.7 | 77.50 | 83.50 |
| 40 | 61/2x 81/2 61/2x 81/2 | 10 | 151/2 | 151/2 | 6.3 | 75.00 95.00 | 81.00 |
| 4a 4b | 616x 816 | 11 | 2514 | 1516 | 7.7 | 105.00 | 111.00 |
| 5 5a 6 6a 7 | 8 x 10 | 111/2 | 20 | 20 | 6.3 | 110,00 | 116.00 |
| ōa e | 8 x 10 10 x 12 | 13 | 251/2 | 20 | 6.8 | 120.00 145.00 | 126.00 |
| 60 | 10 x 12 | 1484 | 2536 | 2536 | 6.3 | 160.00 | 151.00 169.00 |
| 7 | 11 x 14 | 1634 | 31 | 251/6 | 6.8 | 170.00 | 179.00 |
| 7a | 11 x 14 | 1734 | 31 | 31 | 6.8 | 185.00 | 194.00 |





FOR general-purpose work in the studio, for use in home portraiture, for speed work with the reflecting type of camera, the Series II is pre-eminent.

Studio workers find that its perfectly flat field

Studio Workers and General Section Workers and groups. Home portrait photographers like its compact construction. However, for portrait work, where the best perspective is desired, it would be advisable to select a Series II Velostigmat a size larger than the plate for which it is listed.

The Series II is versatile, and its usefulness is not confined to portrait work alone. It is admirable for copying, enlarging, and view work and is also suitable for commercial work when slightly stopped down.

| No. | Size | Equiv. Focus | In Barrel | In Studio | In Betax |
|-------|-------------------|------------------|----------------|--------------|------------------|
| - 0 - | - 21/4x 31/4 - | - 31/2 in | \$22.50 | 1,000 | \$24.50 29.00 |
| 1 | 334x 434 4 x 5 | 5 in. | 25.00 40,00 | | 46,00 |
| 3 | 5 x 7 | 714 in. | 50,00 | | 59,00 |
| 3a | 5 x 8 | 814 in. | 72.50 | | 81.50 |
| 5 | 6½x 8½ 8 x 10 | 9½ in. 12 in. | 105.00 | \$146.50 | 111.00 |
| 6 | 8 x 10 10 x 12 | 14 in. | 185,00 | 190.00 | 140.00 |
| 7 | 11 x 14 | 16 in. | 240.00 | 245.00 | |
| | | | 365.00 | 366.00 | |

A diffusing device supplied on the five larger sizes at ten dollars each extra.



Series III f9.5

A WIDE angle lens is an absolute necessity to the studio or photographic organization endeavoring to maintain a complete photographic service. With a lens of this type it is possible to obtain satisfactory photos of buildings in narrow streets, interiors, banquet groups, and all work in confined space with virtually no distortion.

Being a corrected anastigmat it gives excellent definition over the entire plate for which it is listed, covering an <u>angle of 90 degrees</u>. Stopping down is only necessary to increase depth of focus.

The exceptional speed of the Series III Velostigmat is a mighty fine asset for focusing in dimly lighted interiors, for making snapshots out of doors and for flash light work.

Finely corrected and attractively finished, the Series III Velostigmat Wide Angle constitutes a mighty fine investment for the progressive studio or commercial photographer.

| No. | Plate Covered at f 9.5 | Equivalent Focus | In Barrel | In Betax Shutter |
|-------|------------------------------|--------------------------------|---------------------------|---------------------------|
| 3 4 5 | 5 x 7 6½x 8½ 8 x 10 | 4.3 in. 5.4 in. 6.25 in. | \$43.50 50.00 65.00 | \$47.50 54.00 71.00 |
| 7 | 11 v 14 | 9 in | 100.00 | 106.00 |



Series IV 16.3

THAT we are able to offer as fine a lens as the Series IV so reasonably is indeed a tribute to modern manufacturing methods.

The Series IV Velostigmat is a perfectly corrected ansatigmat, sharply covering the plate for which it is listed at full aperture and working at the high speed of fo.3. It is sustable for commercial, architectural, landscape and view work and home portaiture where the lighting is good. For copying and enlarging the Series IV Velostigmat is a consistent producer of results.

This lens in the smaller sizes can be supplied in cells or in Wollensak shutters for fitting to practically all makes of hand cameras. There is no charge for this fitting.

Where speed or convertibility is not required, this lens would make an excellent choice,

| No. | Size | Equiv. Focus | In Cells | In Barrel | In Betax |
|-------------------|---|--------------------------------------|-------------|----------------------------------|----------------------------------|
| 0 | 214x 314 184x 214 | 3½ in. | \$12.50 | \$20.50 | \$22.50 |
| 1 | 314x 414 | 5 in. | 13.50 | 21.50 | 23.50 |
| 2 | 4 x 5 | 5¾ in. | 14.50 | 22.50 | 26.50 |
| 2A 3 4 5 | 2½x 4½ 3½x 5½ 5 x 7 6½x 8½ 8 x 10 | 6½ in. 7¼ in. 9½ in. 12 in. | 15.00 | 23.00 32.50 50.00 70.00 | 27.00 39.50 56.00 79.00 |





Velostigmat Process and Prieme

THE exceptional chromatic qualities of the Velostigmat Process make it ideal for four-color process work when used at smaller apertures. The precise anastigmatic corrections adapt it admirably to all line and half-tone work where extreme precision is desired

Although designed for the photo engraver, this lens should also interest commercial photographers because its flat field, even illumination and perfect covering power answer the need for ideal copying. enlarging, reducing, etc.

The front lens cell is threaded to receive the Wollensak prisms which are supplied in the sizes listed below. These prisms are accurately ground and polished and made of the finest optical glass. All Process lenses are slotted for waterhouse

stops, with revolving rings to cover when not in use.

| No. | Equiv- alent Focus | Speed | Plates Covered for Re- duction | Plates Cov'd for full Size Copy | Price | Size of Prism to fit | Price of Prism* |
|-----------------------|---|--|--|--|---|------------------------------------|--------------------------------------|
| 4 5 6 7 9 | 10½ in. 14 in. 16 in. 19 in. 25 in. 30 in. | f 10 f 10 f 10 f 10 f 10 f 10 | 6½x8½ 8 x10 10 x12 12 x15 16 x20 20 x24 | 10x12 11x14 12x15 14x17 20x24 24x30 | \$84.50 112.50 135.00 157.50 225.00 326.50 | 2 in. 2½ in. 3 in. 3½ in. | \$67.50 75.00 112.50 135.00 |

*Extra charge for fitting Prisms to Lenses of other makes.



EXTREME WIDE ANGLE

Series IIIa 112.5

THE genuine merits and unlimited possibilities of the Series IIIA Extreme Wide Angle lens has gained for it a host of enthusiastic friends.

Its speed, extreme angle, reserve covering power and moderate price, offer a combination of qualities that should prove of real interest to the commercial photographer. For banquet camera work where space is limited and a short focus lens required, the Series III awill make a strong appeal.

The Series IIIa has an angle of view of 90 degrees and gives good definition at full aperture; wiry sharpness available when the diaphragm is stopped down (which is essential for depth of focus). Because of its large circle of illumination this lens can be used on a plate a size larger than listed by scopping down the diaphragm which then affords an angle of approximately 100 degrees.

| No. | Size | Larger Plates Smaller Stops | Equiv- alent Focus | In Barrel | In Betax Shutter |
|-----|----------|--------------------------------------|--------------------------|--------------|------------------------|
| 3 | 5 x 7 | 6½x 8½ | 4 % in. | \$23,50 | \$27.50 |
| 4 | 616x 816 | 8 x 10 | 5% in. | 30,00 | 36.00 |
| 5 | 8 x 10 | 10 x 12 | 6¼ in. | 33,50 | 39.50 |
| 6 | 10 x 12 | 11 x 14 | 7½ in. | 42,00 | 48,00 |
| 7 | 11 x 14 | 14 x 17 | 9 in. | 52,50 | 58,50 |
| 8 | 14 x 17 | 17 x 20 | 11 in. | 65,00 | 74,00 |



VITAX

WHILE the Vitax is not a general-purpose studio lens like the Series II, it is particularly suited to portrait work and child photography.

In making child portraits and baby pictures speed of lens is all-important. The Vitax works at f3.8 a practical speed for a portrait lens. With this rapidity, snapshot exposures in the studio are entirely practical.

Vitax portraits, particularly large heads and busts, have a rounded, standing-out quality that is life-like and beautiful. This effect is due in part to the improved Petzval formula of the lens. Of value, too, to the portrait photographer is the diffusing device which gives a slight softness when desired.

If your light is poor, your negatives under timed; if you desire a nicer quality in your portraits; if you want certain success in photographing the youngsters—consider the Vitax Portrait f3.8.

| No. | Focus | Lens Diam. | Speed | In Barrel | In Studio Shutter |
|-----|---------|---------------|-------|--------------|----------------------|
| 3 | 10 in. | 3 in. | f 3.8 | \$105.00 | \$110.00 |
| 4 | 13½ in. | 314 in. | f 3.8 | 135.00 | 140.00 |
| 5 | 16 in. | 414 in. | f 3.8 | 185.00 | 186.00 |
| 7 | 20 in. | 438 in. | f 5 | 200.00 | 201.00 |

VITAX EXTENSION LENS to be used with 16" focus, increasing focus to 20", \$57.50



VERITO

Diffused Focus f4

THE pioneer of soft focus lenses. The Verito with its speed, convertible feature and soft focus quality makes it an indispensable tool to the artist-photographer and pictorialist.

Any degree of softness or sharpness may be ob-

tained by simply changing the size of the diaphragm aperture. Definition is not destroyed, but pleasingly subdued so that retouching is practically eliminated. The rear element may be used alone. This gives a slightly different quality of diffusion and being longer in focus than the doublet makes it ideal for longer in focus than the doublet makes it ideal for the longer you use it the more delighted you will be with its infinite possibilities.

When projecting thru the Verito, the harshest and most wiry negatives are made to breathe a softness of exceptional beauty. In enlarging as in making negatives, the softness is controlled by the diaphraem.

| No. | Size | Equiv. Focus | Rear Focus | In Barrel | In Studio | In Betax |
|----------|------------------|----------------------|------------------|------------------|------------------|------------------|
| *A *B | 31/4x 41/4 | 5 in. | 10 in. | \$22.50 25.00 | | \$24.50 29.00 |
| 1 | 31/4x 41/4 | 61/2 in. 61/8 in. | 14 in. 10 in. | 28,50 | | 34.50 |
| 2 3 | 4 x 5 5 x 7 | 734 in. 834 in. | 11 in. 14 in. | 32.50 42.50 | | 41.50 53.00 |
| 5 7 | 6½x 8½ 8 x 10 | 11½ in. 14½ in. | 20 in. 24 in. | 60.00 85.00 | \$65.00 90.00 | |
| 7 | 11 x 14 | 18 in | 30 in | 110.00 | 111.00 | |

*Size A and B, f6-all others f4.

Veritos of special speed 5" focus or shorter in standard Barrel \$25.00.



Verito Extension Lens

THIS is a complete front combination for the 18" focus Verito. It interchanges with the regular front lens and increases the focus to 22½" thus offering a long focus portrait lens at moderate cost. Price complete with mount \$20,00.

Verito for Auto Focus Enlargers

Enlargers with the auto focus features can be equipped with the Verito and still retain the automatic arrangements. To do this it is necessary to send the anastigmat lens from the enlarger to the plant so the focus of it may be exactly duplicated in the Verito.

VOLTAS f8

WHERE high speed and fine corrections are not essential, the inexpensive Voltas will adequately serve the purpose. It is an all-round lens, particularly adapted to landscape, view and commercial work. While fair detail is rendered at full opening, the Voltas must be stopped down in order to insure sharp definition to the extreme corners of the plate. The Voltas is convertible, the single elements may be used alone with smaller stops.

| No. | Size | Equivalent Focus | In Barrel | In Betax Shutter |
|-----|----------|---------------------|--------------|---------------------|
| 1 2 | 334x 434 | 5 in. | \$14.50 | \$16.50 |
| | 4 x 5 | 6½ in. | 15.00 | 19.00 |
| 1 | 5 x 7 | 8 in. | 17.00 | 21.00 |
| | 6½x 8½ | 10½ in. | 25.00 | 31.00 |
| | 8 x10 | 12½ in. | 34.50 | 43.50 |
| 6 7 | 10 x12 | 16 in. | 58.50 | 64.50 |
| | 11 x14 | 18½ in. | 64.00 | 73.00 |

WOLLENSAK RAY FILTER

THE Wollensak ray filter requires but three times normal exposure and will produce beautiful results in cloud, landscape and flower studies, as well as in compensation work

| No. | Will Fit Lens Mounts from | Price | No. | Will Fit Lens Mounts from | Price |
|-----------------------|--|--|------------------------|--|--|
| 1 2 3 4 5 | 1 ½ in. to 1 ½ in. 1 ½ " " 1 ½ " 1 ½ " 1 ½ " 1 ½ " 2 " 2 ½ " 2 ½ " | \$2.50 2.75 3.00 3.50 3.75 | 6 7 8 9 10 | 296 in. to 256 in. 214 " 33 " 316 " 336 " 416 " 496 " | \$4.50 5.25 6.75 7.50 9.00 |

Prices of indestructible Filters of natural yellow glass upon request.



BETAX GAMMAX DELTAX



FOR those who require extreme accuracy in exposures and simple sturdy construction to withstand hard usage, these improved shutters will make a strong appeal.

An outstanding feature in this new line of shutters

is our gearless, pumpless retarding mechanism which is simple in construction and positive in action assuring accurate and unvarying speeds. Metal diaphragm leaves and shutter blades are

incorporated in these models which are ideal for enlarging where heat is intense.

The Betax, Gammax and Deltax shutters are automatic in operation and can be released either with the wire release, or bulb and hose, (with the aid of a bulb attachment). Finished in black lacquer with gold engravings.

| No. | Opening | Opening | Outside | Inside | Betax | Gammax | Deltax |
|----------------------------------|---|---|--|---------------------------------------|---|------------------------|----------------|
| ‡0 *1 *2 †3 †4 †5 | 154 in. 154 in. 154 in. 154 in. 234 in. | 21 in. 1 k in. 1 k in. 1 k in. 1 k in. 2 k in. 2 k in. 2 k in. | 155 132 132 133 233 233 353 432 | 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | \$10,00 10,00 12,00 15,00 18,00 -22,50 | \$5.00 6.00 7.00 | \$4.50 5.50 |

STUDIO SHUTTER

A BETWEEN-the-lens type of shutter that is practically noiseless. It has bulb exposure only and is supplied with wire release as standard equipment, or with attachment for bulb and hose at \$2.50 extra.

at \$2.50 extra.

Exposures of any duration longer than one-fifth second may be had by maintaining pressure on the wire release or bulb.

| No. | Light Open'g | Lens Open'g | Price | No. | Light Open'g | Lens Open'g | Price |
|-----|----------------------|--------------------|------------------|-------|-------------------------------|--------------------|------------------|
| 1 2 | 2 is in. 2 is in. | 211 in. 211 in. | \$15.00 17.50 | *5 | 3½ in. 4½ in. bulb - an | 3 44 in. 45 in. | \$22,50 25,00 |
| 3 | 2 1 in. | 311 in. | 20.00 | *With | hall - an | d tube | only |

No flanges supplied on Studio Shutters.

LENS BARRELS

EQUIPPED with iris diaphragms made of metal that will withstand the heat of the enlarging lamp.

| No. | Light Aperture | Price | No. | Light Aperture | Price |
|-------|--------------------|------------------------|-----|--------------------|---------------------------|
| 1 2 2 | % in. 1% in. | \$8.00 8.00 8.00 | 6 7 | 111 in. 211 in. | \$12.00 13.50 15.00 |
| 4 5 | 1 % in. 1 1 in. | 9.00 | 10 | 3 % in. 3 % in. | 20.00 24.00 |

Prices include flanges.

STANDARD FLANGES LENS CAPS

| hread Diam. Price | Thread Diam. | Price | | side am. | | | | | | Price |
|--|--------------------------------------|---|--------------------------|-------------|-------|--|--|--|--|--|
| \$.50 \$.50 \$.60 \$.65 \$.80 " 1.00 | 213" 213" 313" 35%" 413" | .\$1.35 . 1.50 . 1.60 . 1.75 . 2.00 . 2.50 | 2** 3** 4** 5** | and | under | | | | | \$.75 1.00 1.25 1.50 1.75 2.00 |

ACCESSORIES

Wire releases, 12" or shorter, 85c; 20", \$1.75; 36", \$3.75.

Bulb attachments to fit every Wollensak Shut-

| ter (State size and type shutter) | \$2.50 |
|------------------------------------|--------|
| Studio bulb with 4' tubing | 1.50 |
| Special diaphragm scales, per set | 1.50 |
| Standard diaphragm scales, per set | 1.00 |
| Lens cleaning tissue—per book | .10 |

(Continued from page 3)

Series Ia Velostigmat

THIS lens is available in a variety of sizes, all of which will cover plates a size larger than listed. In addition to the advantages of triple convertibility, the doublet is a perfect anastigmat. The flat field, exceptionally large circle of illumination and the fine anastigmatic corrections of the Series Ia

the fine anastigmatic corrections of the Series Ia Velostigmat lens makes it ideal for banquet cameras.

The following table lists the sizes that are recom-

mended for these cameras:

| No. | Size | Focus | Speed | Plates covered with smaller stop |
|----------|----------------------|------------------------------|---------------------------------|-------------------------------------|
| 3b 3c | 5 x 8 | 814" | 6.8 | 7x11 |
| 4 | 614x 814 | 834" | 6.8 7.7 6.3 6.8 7.7 | 7x11 5x12 |
| 4a | 61/2x 81/2 | 10* | 6.8 | 5x12 |
| 4b 5a | 61/2x 81/2 8 x 10 | 10** 11** 13** 14** | 7.7 | 5x12 7x17 |
| 6 | 10 x 12 | 14" | 6.8 7.7 6.3 | 8x20 |
| 6a 7 | 10 x 12 11 x 14 | 1614" | 6.8 | 8x20 12x20 |



Retouching Glasses

MADE of fine clear glass, optically ground and polished, assuring fine vision without objectionable color-fringes, exceptionally high magnifications. Fitted into highly polished Rhodium plated frame with attractive vulcanized fiber handle. 2\(\frac{3}{2}\)" diameter...\(\mathbb{S}\).175 \quad 3\(\frac{3}{2}\)" diameter...\(\mathbb{S}\).125

 2½" diameter....\$1.75
 3½" diameter....\$2.25

 3" diameter.... 2.00
 4" diameter.... 2.75

 5" diameter.....\$4.00

Reducing Glasses

A BICONCAVE lens used to show how photographs will reduce for reproduction. Supplied in the same style frame and handle as the retouching glasses.

3" diameter.....\$3.00

Tripod Magnifier

A HANDY magnifier for the studio, home and field use. Excellent glass for focusing and examining prints and negatives. Fine lenses give excellent illumination and clear definition. Mounted in stand with screw focusing mount. Magnification 7½X.



THE distance, in inches, required from lens to subject when making portrait of average head of 9 inches.

| Focus of Lens Used | | Heights of Image on Ground Glass | | | | | | | | | | | |
|-----------------------|-------|----------------------------------|-------|-------|-------|-------|-------|-------|------|--|--|--|--|
| | 1 in. | 2 in. | 3 in. | 4 in. | 5 in. | 6 in. | 7 in. | 8 in. | 9 in | | | | |
| 2 | 20 | 11 | | 77 | | | 190 | 7 | | | | | |
| 3 | 30 | 17 | 12 | | | | | | | | | | |
| 3 4 5 | 40 | 22 | 16 | 14 | | | | 100 | | | | | |
| 5 | 50 | 28 | 20 | 18 | 14 | | | | | | | | |
| 6 7 8 | 60 | 33 | 24 | 21 | 17 | 15 | | | | | | | |
| 7 | 70 | 38 | 28 | 25 | 19 | 18 | 16 | | | | | | |
| 8 | 80 | 44 | 32 | 28 | 22 | 20 | 18 | 17 | | | | | |
| 9 | 90 | 50 | 36 | 32 | 25 | 23 | 21 | 19 | 18 | | | | |
| 10 | 100 | 55 | 40 | 35 | 28 | 25 | 23 | 21 | 20 | | | | |
| 11 | 110 | 61 | 44 | 39 | 31 | 28 | 25 | 23 | 22 | | | | |
| 12 | 120 | 66 | 48 | 42 | 34 | 30 | 28 | 25 | 24 | | | | |
| 13 | 130 | 72 | 52 | 46 | 36 | 33 | 30 | 27 | 26 | | | | |
| 14 | 140 | 77 | 56 | 49 | 39 | 35 | 32 | 29 | 28 | | | | |
| 15 | 150 | 83 | 60 | 52 | 42 | 38 | 36 | 32 | 30 | | | | |
| 16 | 160 | 88 | 64 | 56 | 45 | 40 | 37 | 34 | 32 | | | | |
| 17 | 170 | 94 | 68 | 60 | 48 | 43 | 39 | 36 | 34 | | | | |
| 18 | 180 | 99 | 72 | 63 | 50 | 45 | 41 | 38 | 36 | | | | |
| 19 | 190 | 105 | 76 | 67 | 53 | 48 | 44 | 40 | 38 | | | | |
| 20 | 200 | 110 | 80 | 70 | 56 | 50 | 46 | 42 | 40 | | | | |

THE distance, in inches, required from lens to subject when making full length pictures of average standing figure of 68 inches.

| Focus of Lens Used | | Heights of Image on Ground Glass | | | | | | | | | | | |
|-----------------------|-------|----------------------------------|-------|-------|-------|-------|--------|-------|-------|--|--|--|--|
| Foet | 2 in. | 3 in. | 4 in. | 5 in. | 6 in. | 7 in. | 8 in. | 9 in. | 10 in | | | | |
| 2 | 70 | 19 | | - | | | | | | | | | |
| 3 | 105 | 71 | | | | | | | | | | | |
| 4 | 140 | 95 | 72 | | | | 111111 | | 200 | | | | |
| 5 | 175 | 118 | 90 | 73 | | 1 | | | 30.0 | | | | |
| 6 | 210 | 142 | 108 | 88 | 74 | | | | 201 | | | | |
| 6 7 8 | 245 | 166 | 126 | 102 | 86 | 75 | | | 7.00 | | | | |
| 8 | 280 | 189 | 144 | 117 | 99 | 86 | 76 | | | | | | |
| 9 | 315 | 213 | 162 | 131 | 111 | 96 | 86 | 77 | 100 | | | | |
| 10 | 350 | 237 | 180 | 146 | 123 | 107 | 95 | 86 | 78 | | | | |
| 11 | 385 | 260 | 198 | 171 | 135 | 118 | 105 | 94 | 86 | | | | |
| 12 | 420 | 284 | 216 | 175 | 148 | 129 | 114 | 103 | 94 | | | | |
| 13 | 455 | 308 | 234 | 190 | 160 | 139 | 124 | 111 | 101 | | | | |
| 14 | 490 | 331 | 252 | 204 | 173 | 150 | 133 | 120 | 109 | | | | |
| 15 | 525 | 355 | 270 | 219 | 185 | 161 | 143 | 128 | 117 | | | | |
| 16 | 560 | 379 | 288 | 234 | 197 | 171 | 152 | 136 | 125 | | | | |
| 17 | 595 | 402 | 306 | 248 | 210 | 182 | 162 | 145 | 133 | | | | |
| 18 | 630 | 426 | 324 | 263 | 221 | 194 | 171 | 154 | 140 | | | | |
| 19 | 665 | 450 | 342 | 277 | 234 | 203 | 181 | 163 | 148 | | | | |
| 20 | 700 | 473 | 360 | 292 | 247 | 214 | 199 | 171 | 156 | | | | |

GUARANTEE

Wollensak lenses are guaranteed to be optically and technically correct. All shutters are warranted to give perfect satisfaction. If any of our products, with proper care, fail to give satisfaction within a year after leaving our factory, we will repair or replace free.

TRIAL PRIVILEGE

Our liberal trial privilege permits a through test before buying. Should a customer be undecided between two types or sizes of lenses, we are willing to send both for comparative test without obligation, through a photographic dealer. The customer, however, is expected to pay the transportation charges when a lens is sent on memorandum.

TERMS

Wollensak lenses are sold only through established photographic stock houses or dealers. If the customer has no local dealer, we will gladly put him in touch with someone conveniently located who can take care of his requirements. All prices are f. o. b. Factory.

ADVISORY SERVICE

Our Service Department is ready and willing to give individual attention to all optical and shutter problems. This service involves no obligation.

OTHER WOLLENSAK PRODUCTS

MOVIE LENSES & ACCESSORIES
PROJECTION LENSES
FIELD GLASSES
MICROSCOPES
MAGNIFIERS
TELESCOPES

